

Ref: CWWD/T/W/05/2023-2024

Date: 20th October 2023

Dear Bidders,

RE: CONSTRUCTION OF WATER HARVESTING FACILITIES AT MIDOINI SECONDARY SCHOOL -RESERVED FOR YOUTH

## TENDER NO. CWWDA/T/W/05/2023-2024

## **ADDENDUM NO.1**

Reference is made to the above subject matter.

Pursuant to clause 10.1 of the Instruction to Tenders(ITT), the following sections of the bidding for the above mentioned tender has been amended as follows:

- SECTION VI Bills of Quantities appearing on page 65-75 be
   Deleted and replace with the enclosed Revised Bill of Quantities
   (Annex I)
- 2. SECTION V (DRAWINGS) The actual drawings and plans are enclosed as Annex II.

ENG. MARTIN TSUMA

Ag. CHIEF EXECUTIVE OFFICER

Tel: No. 041 - 2315230 0731 231523 Email: info@cwwda.go.ke Website: www.cwwda.go.ke complaints@cwwda.co.ke

## **BILLS OF QUANTITIES**

ITEM	DESCRIPTION	UNIT	QUANTITY	AMOUNT	AMOUNT
				(KShs.)	(KShs.)
1	Provisional Sums				
	BILL No. 1: GENERAL ITEMS				
1	Item covers elements of work which be considered as proportional to the to the are not to quantities of the permanent works		1		
	Contractual requirements				
	Total value should conform to clause 60(I) partII conditions of contract				
1.1	Insurance of the works	SUM	L.S		
1.2	Third party insurance	SUM	L.S		
1.3	Signboards provide, erect ,maintain and remove on completion 1no. Signboards in accordance to specifications /as directed by the Site Engineer (Use APPROVED HARDWOOD)	Nr	1		
#.# ==	Specified requirements				
1.4	Allow for supervision by Coast Water Works Development Agency Staff	SUM	1	450,000.00	450,000.00
1.5	Fuels for vehicle for the Supervision staff for the entire duration of the project	SUM	1	300,000.00	300,000.00
1.6	Allow for contractors overheads for above items 1.4 and 1.5	%		750,000	

	Attendance upon the Engineer's staff			
1.70	Establishment of Contractors camp office, facilities, etc and provision of all equipment that will be required during the entire Contract period.	Sum		
	TOTAL CARRIED TO COLLECTION PAGE			
	BILL NO. 1.0: COLLECTION			
	BILL NO. 1.0. COLLEGIA			
	From Page 1			
	From Page 2	L rese		
	BILL NO 1: TOTAL CARRIED TO SUMMARY	DACE		×

BILL NO.	2: CIVIL WORKS				
ITEM	ITEM DESCRIPTION	UNIT	QUANTIT Y	RATE	AMOUNT (SHS)
2.1	Procure and Install 2Nr PVC plastic tank of 24m3 each. The size should be of short and wide base due to roof hieght	Nr	2		
2.2	Procure and Install 2Nr PVC plastic tank of 10m3 each to be placed at the Platform	Nr	2		
2.3	Supply and fix Fiscia board 8" X 1" to an existing roof to hold gutters	М	80		
2.4	Provide and apply relevant paint to fixed fascia boards as may be directed by the project supervisor	Item	1		
2.5	Supply and install strategically, DN 140mm half round PVC plastic 5m long gutters to detail capable of holding and transmitting rain water safely	Nr	150		
2.6	Supply and fix standard gutter support brackets DN 140mm spaced 1.0m apart	No	120		
2.7	Supply and fix, strategically DN 140mm gutter stop end	No.	8		
2.8	Supply and fix click fit with running outlet PVC 140 x 75 mm	No	8		
2.9	Provide and install DN 90mm HDPE PN10 pipes for water supply reticulation within the institution, together with all necessary pipe fittings	Sum	1		
2.10	Supply and install 90mm PVC down pipe	М	100		
2.11	Supply and install 90mm PVC down pipe bends	No.	8		
2.12	Supply and install 90mm PVC down pipe clips	No	8		
2.13	Supply and install 3/4" pegler tap	No	. 15	1 700	
2.14	Supply and install 3/4" GI union	No	8	1.	
2.15	Supply DN90mm Elbows	No	8	9	直出.
	SUB TOTAL				
2.2	BASE SLAB				
2.21	Procure and supply machine cut natural stone blocks	No	1000		

2.22	Excavate void to create space for slab foundation	M3	20	
2.23	Procure and supply Ballast	Ton	20	
2.24	Procure and supply sand	Ton	60	
2.25	Procure and supply Hard core	Ton	60	14,14,2
2.26	Construct a circular block wall 1.5 dia to form wall and 2 no. diagonal inside walls intersecting at centre of the tank base. The base should be 0.5m a.g.l.	M2	24	
2.27	Procure and supply Wire mesh(4x8 feet)	No.	8	
2.28	Fill hardcore in the circular block wall and compact well with sand.	М3	150	
2.29	Construct a reinforced top slab of 50mm supported by a BRC No. A142 and leave to cure well.	M3	4	
				MACON L
	SUB TOTAL			
	GRAND TOTAL CARRIED TO SUMMARY PAGE			

ILL o. 3	CONSTRUCTION OF RC TOWER FOR 2Nr STORAG	E TANKS	5		
Bill No.	RC TOWER 1Nr. FOR WATER STORAGE TANKS				
	DESCRIPTION	UNIT	QTY	UNIT RATE	TOTAL
1.00	Site Clearance, Excavation and Earthworks.			(KES)	(KES)
	Excavation including maintaining and supporting sides and keeping free from water, mud and fallen materials by bailing, pumping or otherwise				
1.10	Prepare site by stripping top 150 mm of soil to remove all debris including sand (if any) from site and carting away spoil	m2	31		
1.20	Excavate trench commencing at reduced levels depth not exceeding 1.50m deep	m3	11		
1.30	Pit excavation commencing at reduced levels depth not exceeding 2.0m deep	m3	28		
1.40	Extra-over for excavation in rock	m3	2		
1.50	Remove surplus excavated material from site	m3	4		
1.60	300 mm thick approved hardcore filling spread, well rammed and compacted in 150mm layers	m3	8		
2.00	Concrete works				1 11
	In situ concrete: Provision and placing. Rate to include for shuttering				
2.10	50mm Thick blinding	m3	2		

Vibrated Reinforced Concrete class 25 (1:1.5:3) with 20m m thick maximum aggregate size .Rate to include for shuttering and formwork.				
Ground beam	m3	5		
Column base	m3	5		
Vibrated Reinforced Concrete class 25 (1:1.5:3) with 20m m thick maximum aggregate size, Rate to include for shuttering and formwork.				
Tie beam	m3	7		
Columns	m3	5		
Reinforcement				
		<del>                                      </del>		
Reinforcement bars (all sizes) as shown on drawings	kg	2,200		
Parapet Walling				
Install parapet walling to tanks 1.2m high using machine cut blocks 200mm	m2	40		
Finishes			iii	
Cement and sand mortar (1:3) rendering in:				
25 mm Thick screed to all columns	m2	11		
25 mm Thick screed to all Beams	m2	11		
15mm plaster to internal sides of parapet walling wall with waterproof cement	m2	30		
	m thick maximum aggregate size .Rate to include for shuttering and formwork.  Ground beam  Column base  Vibrated Reinforced Concrete class 25 (1:1.5:3) with 20m m thick maximum aggregate size, Rate to include for shuttering and formwork.  Tie beam  Columns  Reinforcement  Reinforcement bars (all sizes) as shown on drawings  Parapet Walling  Install parapet walling to tanks 1.2m high using machine cut blocks 200mm  Finishes  Cement and sand mortar (1:3) rendering in:  25 mm Thick screed to all columns  25 mm Thick screed to all Beams	m thick maximum aggregate size .Rate to include for shuttering and formwork.  Ground beam m3  Column base m3  Vibrated Reinforced Concrete class 25 (1:1.5:3) with 20m m thick maximum aggregate size, Rate to include for shuttering and formwork.  Tie beam m3  Columns m3  Reinforcement  Reinforcement ars (all sizes) as shown on drawings kg  Parapet Walling  Install parapet walling to tanks 1.2m high using machine cut blocks 200mm  Finishes  Cement and sand mortar (1:3) rendering in:  25 mm Thick screed to all columns m2  25 mm Thick screed to all Beams m2  15mm plaster to internal sides of parapet walling wall m2	m thick maximum aggregate size .Rate to include for shuttering and formwork.  Ground beam m3 5  Column base m3 5  Vibrated Reinforced Concrete class 25 (1:1.5:3) with 20m m thick maximum aggregate size, Rate to include for shuttering and formwork.  Tie beam m3 7  Columns m3 5  Reinforcement  Reinforcement bars (all sizes) as shown on drawings kg 2,200  Parapet Walling  Install parapet walling to tanks 1.2m high using machine cut blocks 200mm  Finishes  Cement and sand mortar (1:3) rendering in:  25 mm Thick screed to all columns m2 11  25 mm Thick screed to all Beams m2 11  15mm plaster to internal sides of parapet walling wall m2 30	m thick maximum aggregate size .Rate to include for shuttering and formwork.  Ground beam m3 5  Column base m3 5  Vibrated Reinforced Concrete class 25 (1:1.5:3) with 20m m thick maximum aggregate size, Rate to include for shuttering and formwork.  Tie beam m3 7  Columns m3 5  Reinforcement  Reinforcement  Reinforcement bars (all sizes) as shown on drawings kg 2,200  Parapet Walling  Install parapet walling fo tanks 1.2m high using machine cut blocks 200mm  Finishes  Cement and sand mortar (1:3) rendering in:  25 mm Thick screed to all columns m2 11  25 mm Thick screed to all Beams m2 11  15mm plaster to internal sides of parapet walling wall m2 30

4.40	15mm plaster to External sides of parapet walling wall with waterproof cement	m2	32	
5.00	Water Supply System			
	PPR pipes PN12.5 including jointing, fittings and fixed as described			
5.10	65mm diameter inlet pipe	nr	1	
5.20	65mm diameter draw off	nr	1	
5.30	65mm diameter overflow pipe Ditto	nr	1	
5.40	65mm diameter scour pipe Ditto	nr	1	
5.50	20mm diameter brass gate valve with wheel and head	nr	1_	
5.60	20mm diameter stop corks	nr	1	
5.70	600x600x6mm heavy gauge steel primed metal manhole cover on slab with and including metal framing all around	nr	1	
5.80	20mm Diameter bars, 'U' shaped to form steps with ends embedded into retaining wall, average length 450mm	nr	8	
	Plastic Tanks 2nr x10,000litres			
5.90	Supply, installation and testing of 2nr Durable plastic Tanks 10,000litres each RC tower10m high	nr	2	
5.10	Allow Sum for plumbing works to interconnect plastic tanks to water supply using 3 inch PPR pipe/hdpe pn12.5	Item	1	
	TOTAL BILL NO. 3 CARRIED TO SUMMARY PAGE			

BILL NO. 4	PROCURE AND INSTALL A 1HP SUBMERCIA	BLE PU	MP		
				7.	
ITEM	DESCRIPTION	UNIT	QUANTITY	RATE	AMOUNT (KShs.)
5	PROCURE ALL NECESSRY FITTINGS AND ACCESORIESA AND INSTALL A 1.0 HP SUBMERCIABLE				
5.1	Procure, deliver all necessary Fittings and accesories and install a 1.0 HP pump. The pump should be of submerciable type, driven by a Solar system with automatic switch Gear, as shall be directed by the project Engineer	Sum			
x = -1 -	These includes, but not limited to, Appropriate Sunverter, Solar modules, Motor, Connectors, support structure and all other necessary fittings, as may be advised by the Site Engineer.		1		
	SUB-TOTAL				

	DESCRIPTION	UNIT	QTY	UNIT RATE	TOTAL
				(KES)	(KES)
	CONSTRUCTION OF 1No. MASONRY UNDERGROUND WATER TANK 50 M3				
1	EXCAVATION AND EARTHWORKS				
1.1	Clear site of bushes,shrubs,,shrubs and burn on site as directed	sm	36		
1.2	Excavate tank base starting from ground level but not exceeding 1.5m deep in coral rock	cm	54		
1.3	Excavate for 1No centre column Base as directed by engineer	cm	0.7		
1.4	Return fill and ram selected excavated material around the tank	cm	16		
1.5	Cart away fro site surplus excavations spoil as directed	cm	38		1
1.6	300mm thick approved hardcore fill in making up levels and compacted	sm	36		
	Quary dust	m2			
	Damp proof membrane	m2			
	CONCRETE WORKS				1
2.1	50mm thick plain concrete class x mix (1;4;8) blinding	sm	36		
2.2	Vibrabrated in situ Reinforced concrete class 20/20 (1:2:4)in.				
	i1)150mm thick floor slab	cm	4.6		
	iii)column base andcolumn	cm	0.3		
	iv)ring beam	cm	0.9		
	roof cover slab	cm	4		
2.3	Formwork				
	i)sides of base column	sm	8	-1	

	ii)sides and edges of floor slab curved on plan150-225	lm	22	
	iii)soffit of roof slab	sm	24	
	iv)rsides and edges of roof slab in ranges of 150m-225mm	lm	23	
	v) sides and soffit of ringbeam	sm	18	
	STEEL REINFORCEMENT			
	HIGH YIELD TENSILE STEEL COLD WORKED bs4461 RATE TO INCLUDE CUTTING,BEDDING AND TYING			
2.4	Floor slab			l la
	i)10mm diameter bars	mts	240	l Hill
	ii)12mm diameter bars	mts	156	
2.5	walling bars			13. 2.2
	i)8mm diabars	m	720	
2.6	column basa and column			
	i)8mm diameter round bar	m	6	
	ii)12mm squire twisted	mts	72	
2.7	roof slab			
	i)10mm diammeter bars	mts	542	
	ii)16mm diammeter bars	mts	24	
2.8	beams			
2.0	i)12mm diammete(R8) bars	mts	72	
	ii) 8mm diammeter bars squire twisted bars	mts	68	
2.9	walling			
	solid concrete block wall curved in plan at 3.02 radius joint with cement motor 1:3 (225 X 300 X 150mm)- W x L x H	sm	48	
4	FINISHES			
4.1	Apply two coats of bituminous paint to floor slab 400mm wide ,before start of walling	lm	17	
4.2	Ditto on top of walling 280mm wide, before roof slab	lm	17	
4.3	seal joint between wall and floor slab,and round column with 2.5x40mm bondex	lm	17	
4.4	50mm thick cement and sand(1:2) plaster o walls internally mixed with water proof cement and finish smooth with water proff cement grout	sm	48	

4.5	50mm thick cement and sand (1:2) on floor screed finished smooth with water proof cement	sm	20		
4.6	30mm thick cement and sand screed (1:3) on top of roof cover slab laid to fall	sm	20		
4.7	25mm thick cement and sand (1:3) plaster to walls externally	sm	50		
4.8	600x600mm precast concrete manhole covers to be fixed in position	no	1		
4.9	fabricate steel ladder 400mm wide with rungs at 250mm centre to centre with lugs fix in tank wall at 900 mm spacing, and painted with alluminium paint before fixing.overal height 3.3m external ladder	no	1		
4.1	ditto,overal height 3.2 high internal ldder	no	1		
4.11	apply tree coats of white emulsion paint to external wall	sm	48		
4.12	apply two coats of gloss paint royal blue in colour	sm	12		
4.13	apply two coats of black bituminous paint to a height of 300 mmfrom ground level	sm	4.8		
4.14	construct masonry valve chambers internal size 1.2 x1.2 m complete with concrete cover	no	2		
5	PIPES AND FITTINGS				
	i)measurement have been to the first chamber to tank inlet	no	1		
	ii)80mm diamer Gi pipe class B	NO	1		
	iii)8mm Gi bend 90 degrees	no	3	7	
	iv)80mm diammeter GI socket	no	3	10.12.51	
	v)80mm diammete union	no	2		
	vi)80mm sluice valve pn 16	no	1	E. L.	
	vii)80mm flages drilled with 4holes	no	2		
5.2	OUTLET PIPE				
	I)80mm diameter PVC pipe class E	no	1		
	ii)80mm diameter PVC bend 90 degrees	no	1		
	iii) 100x80 mm reducing socket	no	1		
	iv) 80mm dia PVC sopcket	no	2		
	v) 80mm diammeter gate valve flanges drilled with 4 holes	no	1		112

	vi) 80mm diameter flanges filled with 4holes complete with 16mm diammeter bolts and nuts 63mm long threats and sunction rubber guskets	no	2		
	vii)80mm diameter coupling vjcouplings	no	2		
	viii)80mm diamete PVC tee	no	2		
5.3	SCOUR PIPE				
	I) 80mm diammeter PVC pipe class B	No	11		
	ii)80mm PVC bend 90 degrees	no	1		
	iii)100mm x80mm diameter reducing socket	no	1		
	iv)80mm diammeter Gi socket	no	2		
	v) 80mm sluice valve drilled with 4 holes	no	1	. 11	
	vi) 80mm diameter flanges drilled with 4 holes complete with 16mm diammeter bolts and nuts 16mm long threads and sunction rubber gasket	no	2		
5.4	OVERFLOW PIPE	913			HE SELECTION
	I) 80mm diammeter PVC nipple 600mm long,threaded one side and welded with puddle flage at middle	no	1		
	ii)80mm Gi bend 90 degrees	no	1	Herry &	
	iii)80mm diammeter gi socket	No	1		
				771	
5.5	VENT PIPE		100 100 100		
3.3	I) 100mm diameter PVC nipple 600mm long threaded both ends and welded with puddle flage at middle	no	2		
	ii) 100mm diameter PVC bend 90 degrees	no	8		
	iii) 100mm diameter PVC Tee	no	4		
	iv) plastic mosquito gauze wire(to be tied at one of the bend with galvanised bidding wire	Lm	1		
6	Allow sum for connection water supply to the end of existing tank	item	1		
	TOTAL CARRIED TO SUMMARY PAGE				

	GENERAL SUMMARY		
	CONTRACT No.		
	NAME OF CONTRACT: CONSTRUCTION OF RAIN SYSTEM FOR MIDOINA SECONDSRY SCHOOL	WATER HA	ARVESTING
	DESCRIPTION	PAGE	AMOUNT
			(KES)
BILL No. 1	PRELIMINARY AND GENERAL ITEMS		
BILL No. 2	CIVIL WORKS AND ACCILARY		
BILL No. 3	CONSTRUCTION OF WATER TOWER		-
BILL No. 4	CONSTRUCTION OF 50M3 MASONRY TANK		
BILL No. 5	PROCUREMENT AND INSTALLATION OF 1.0HP SUBMERCIABLE PUMP		
	Total of Bills inclusive of Provisional Sums and Prime Cost Sums	A	
	Sub-Total(A))	A	
	Allow for all Local Taxes and Duties including 16% VAT on "B" above	В	
	Bid Price (A+B) (Carried forward to Letter of Bid)	С	
Amount in \	Words:		
Bidder's Na	me:		
Bidder's Sig	nature:		
Date:			
	4		
Official Ruber Stamp			

